



図面／規格  
【ノルトロックワッシャー】

$\phi d$

NL3 ~ NL8  
 $\phi d \pm 0.1\text{mm}$

NL10 ~ NL42  
 $\phi d \pm 0.2\text{mm}$

NL45 ~ NL130  
 $\phi d +0.5/-0.0\text{mm}$




$\phi D$

$\phi D$

NL3 ~ NL24  
 $\phi D \pm 0.2\text{mm}$

NL27 ~ NL42  
 $\phi D \pm 0.3\text{mm}$

NL45 ~ NL130  
 $\phi D +0.0/-2.0\text{mm}$



T

T

NL3 ~ NL42  
T  $\pm 0.25\text{mm}$

NL45 ~ NL130  
T  $\pm 0.75\text{mm}$

※厚さ(T) 6.6mmの  
ワッシャーの厚さ許容差は、  
+0.0/-0.5mmです。

単位:mm

型 式	$\phi d$ (内径)	$\phi D$ (外径)	T(厚さ)			型 式	$\phi d$ (内径)	$\phi D$ (外径)	T(厚さ)		
			鉄 (SC材)	SUS	254 SMO				鉄 (SC材)	SUS	254 SMO
NL3	3.4	7.0	1.8	2.2	2.2	NL36	37.4	55.0	5.8	6.8	5.8
NL3.5	3.9	7.6	1.8	2.2	2.2	NL39	40.4	58.5	5.8	6.8	5.8
NL4	4.4	7.6	1.8	2.2	2.2	NL42	43.2	63.0	5.8	6.8	-
NL5	5.4	9.0	1.8	2.2	2.2	NL45	46.2	70.0	7.0	6.8	-
NL6	6.5	10.8	1.8	2.2	2.2	NL48	49.6	75.0	7.0	6.8	-
NL1/4"	7.2	11.5	2.5	2.2	2.2	NL52	53.6	80.0	7.0	9.0	-
NL8	8.7	13.5	2.5	2.0	2.0	NL56	59.1	85.0	7.0	9.0	-
NL3/8"	10.3	16.6	2.5	2.0	2.0	NL60	63.1	90.0	7.0	9.0	-
NL10	10.7	16.6	2.5	2.0	2.0	NL64	67.1	95.0	7.0	9.0	-
NL11	11.4	18.5	2.5	2.2	2.2	NL68	71.1	100.0	9.5	9.0	-
NL12	13.0	19.5	2.5	2.0	2.0	NL72	75.1	105.0	9.5	9.0	-
NL1/2"	13.5	19.5	2.5	2.0	2.0	NL76	79.1	110.0	9.5	9.0	-
NL14	15.2	23.0	3.4	3.0	3.0	NL80	83.1	115.0	9.5	9.0	-
NL16	17.0	25.4	3.4	3.0	3.0	NL85	88.1	120.0	9.5	-	-
NL18	19.5	29.0	3.4	3.2	3.2	NL90	92.4	130.0	9.5	-	-
NL3/4"	20.0	30.7	3.4	3.2	3.2	NL95	97.4	135.0	9.5	-	-
NL20	21.4	30.7	3.4	3.0	3.0	NL100	103.4	145.0	9.5	-	-
NL22	23.4	34.5	3.4	3.2	3.2	NL105	108.4	150.0	9.5	-	-
NL24	25.3	39.0	3.4	3.2	3.2	NL110	113.4	155.0	9.5	-	-
NL1"	27.9	39.0	3.4	3.2	3.2	NL115	118.4	165.0	9.5	-	-
NL27	28.4	42.0	5.8	6.8	5.8	NL120	123.4	170.0	9.5	-	-
NL30	31.4	47.0	5.8	6.8	5.8	NL125	128.4	173.0	9.5	-	-
NL33	34.4	48.5	5.8	6.8	5.8	NL130	133.4	178.0	9.5	-	-